1 Ea. New current year model or latest year end production model Crawler Tractor (Low Ground Pressure) with power angle, power tilt inside mounted blade; meeting the following specifications in accordance with manufacturer's standard published specifications.

Engine: Diesel; 96 net flywheel horsepower; 24 or 12 volt electric system; 55 amp alternator.

Transmission: Type: Hydrostatic drive.

Steering: Wet disc, oil bath type, or hydraulically controlled (with single lever control).

Service Brakes: Shall be oil bath. Parking brake to be provided.

Undercarriage: Track gauge to be at least 70", grousers to be a minimum 26" wide low ground pressure. Seven (7) bottom rollers per side and life-time lubricated. Tractor shall have sealed and lubricated track chains and hydraulic track adjusters. Ground clearance 13" or more. Must have at least 91" of track on ground.

Blade: Power Angle and Tilt, at least 120" wide and at least 36" in height with a raise height of at least 31" and tilt 17" to either side with float position. A blade angle of 25 degrees minimum.

Ripper: 3 shanks minimum.

Operating Weight: At least 21,300 lbs without ripper.

Other Equipment: ROPS cab w/heater & defroster; air conditioners (not roof mounted); work lights; back-up alarm; track guiding guards, full length; drawbar; engine side panels; front pull hook; radiator sand screen or severe service radiator; engine and transmission guard; armchair type suspension seat with seat belt; vandalism protection with locks; instrument gauges to monitor all critical functions; cold weather starting aid. High intensity strobe light, work lights.

Warranty: 5 year/3,000 hours full machine warranty to include oil analysis (no deductible).

Vendor to furnish two (2) sets of parts books, service manuals, technical manuals and operators' manuals with unit when delivered.

Vendor must have parts and service within 100 miles of delivery point within the state of Alabama. Delivery date may be a factor in making award. Must furnish three (3) sets of keys.