

- 1 Ea. New latest model Crawler Tractor with power angle, power tilt inside mounted blade; meeting the following specifications in accordance with manufacturer's standard published specifications.

<u>Engine:</u>	Diesel; 115 net flywheel horsepower; 24 or 12 volt electric system; 55 amp alternator.
<u>Transmission Type:</u>	Hydrostatic drive.
<u>Steering:</u>	Wet disc, oil bath type, or hydraulically controlled.
<u>Service Brakes:</u>	Shall be oil bath. Parking brake to be provided.
<u>Undercarriage:</u>	Track gauge to be at least 70", shoes to be at least 28" wide. Seven (7) bottom rollers per side and life-time lubricated. Tractor shall have sealed and lubricated track chains and hydraulic track adjusters. Ground clearance 14" or more. Must have at least 103" of track on ground.
<u>Blade:</u>	Power Angle and Tilt, at least 132" wide and at least 37" in height with a raise height of at least 36" and tilt 18" to either side with float position. Blade to angle at least 25 degrees to either side.
<u>Operating Weight:</u>	At least 28,000 lbs.
<u>Ripper:</u>	Multi-Shank (3 minimum) Ripper
<u>Other Equipment:</u>	ROPS cab w/heater & defroster; air conditioners; work lights; back-up alarm; track guiding guards, full length; drawbar; engine side panels; front pull hook; radiator sand screen or severe service radiator; engine and transmission guard; armchair type suspension seat with seat belt; vandalism protection with locks; instrument gauges to monitor all critical functions; cold weather starting aid.
<u>Warranty:</u>	5 year/3,000 hours full machine warranty to include oil analysis (no deductible).

Any variations from these specifications to be listed on a separate sheet of paper and attached to bid.

Vendor to furnish two (2) sets of parts books, service manuals, technical manuals and operators' manuals with unit.

must
have three (3) sets of keys. Delivery date may be a factor in making award.